



Product Code: 923642

## DESCRIPTION

- Metal Cable tie base for fixing directly to Concrete, Steel & Timber.
- Slots enable use as cable tie base
- 3x fixing holes for versatility,
- Thumb friendly, rounded corners, 20mm wide, and pliable for easy installation
- Side notches can also be used to thread steel ties, useful for securing larger bundles of cables.
- Uniquely versatile - for shaping as required
- Easy to later add or remove cable(s) - Can be opened/closed to 5x


## TOOLS

- SPIT Pulsa 800 (To be used with the flat magnetic pin guide (014642))
- \*Cables Ties not included\*

## SPECIFICATION

- Pre-drilled hole of 5.7mm for screw fixing option
- >1200°C melting point
- Compliant with BS7671 and BS5839-1 requirements
- BSEN50200:2000; & BS8434-1:2003
- 20mm wide side-tabs & pliable gauge combines for quick and easy folding


## DIMENSIONS (mm):



(L) 56mm x (W) 20mm x (H) 8mm (folded - max height) 5.7mm diameter pre-drilled hole in base

## PIN SELECTOR GUIDE

- Ensure that the embedment depth is adapted to the recommended load requested for the accessories
- HC6FH can also be used in conjunction with the U clip. See pin size as guide.

PIN SELECTOR GUIDE:							
	C6-20	C6-25	C6-30	HC6-15	HC6-17	HC6-22	HC6-27
Concrete C20/25	■	■			■	■	
Concrete C30/37	■				■		
Concrete C40/50				■	■		
Prestressed / Prefabricated concrete				■	■		
Solid Brick		■				■	
Hollow Brick rendered		■				■	
Hollow concrete block		■				■	
Calcium silicate block		■				■	
Steel				■			
Timber							■